

# Adventure Buggy Company

---

## INSTRUCTIONS FOR CORRECT USE

### TODDLER SEAT MK3



## **INSTRUCTIONS FOR TOP – MOUNTED TODDLER SEAT (MK3)**

**CAUTION: SEAT MUST ONLY BE USED WITH “FLAT-TOP” SUN CANOPIES.**

**16kg MAXIMUM WEIGHT CAPACITY FOR TODDLER SEAT**

### **INSTALLING THE SEAT**

#### ***A) FIXING THE ALIGNMENT OF YOUR EXTENDIBLE HANDLE***

**Tip:** Silicon spray will free up your handle to slide easily.

**Note:** If your extendible handle is difficult to adjust the height, it is likely that the extendible handle is not correctly aligned.

**Remove the handle.** Place the ends of the chrome handle against the openings at the top of the frame (where the handle enters). If these are not aligned or do not meet the ends of the tube of the frame - then it is not aligned correctly.

#### **To re-align;**

- 1) The chrome handle should meet up evenly and enter the top of the buggy frame easily.
- 2) First check whether the chrome handle (sliders) are parallel. If it isn't then simply expand so that it is parallel.
- 3) Un-dome the top 4 x domes of the sling (2 x each side) and disconnect the sun canopy..
- 4) "tweak" the buggy frame by pulling apart the top ends of the tube (where the handle enters), and re-check that the handle meets the top of the buggy frame.
- 5) Return handle to the buggy frame and re-dome baby sling. Spray some silicon onto chrome handle.

#### ***B) INSTALLING THE TODDLER SEAT ONTO THE EXTENDIBLE HANDLE***

- 1) With the seat facing you, enter the extendible handle sliders into the tube brackets of the seat. As described above, it is necessary that your handle meets these openings. If the handle doesn't - repeat the process described above (A).
- 2) Slide the handle through the toddler seat openings (note: you will have to depress the safety buttons on the handle to complete the process).

#### ***C) INSTALLING THE TODDLER SEAT / HANDLE ONTO THE BUGGY***

- 1) Ensure your sun canopy is out stretched into the sun protection position.
- 2) Slide the Toddler seat half way up the handle
- 3) With the extendible handle now installed on the toddler seat, return the handle/seat combination to the buggy.
- 4) Ensure the safety buttons have clicked into the safety holes of the buggy frame, (which is the fully extended position of the handle).
- 5) **IMPORTANT:** Slide the toddler seat down the handle so that the seats tube-bracket's are flush with the TOP of the buggy frame.

**NOTE: The toddler seat is required to rest against the top of the buggy frame for correct balance and stability. The toddler seat must be positioned directly over the buggies rear wheels.**

- 6) Tighten the screw handles under the buggy frame to secure the handle into place.

**Note:** It is suggested that the handle be used in the fully extended position with the MK3 toddler seat installed. The extra length provides greater leverage and control of the additional buggy weight. Satisfactory leg room for the toddler in the MK3 seat also benefits with the handle fully extended.

To remove the seat - simply reverse the above instructions for installing.

### ***D) PLACING YOUR CHILD IN THE TODDLER SEAT***

- 1) Apply the brake
- 2) Remove the safety bar of the toddler seat. Simply depress the spring buttons and pull the safety bar out to remove (note: you may have to un-dome the front crotch “tongue”)
- 3) Place your child in the seat.
- 4) Return the safety bar into its safe position. Ensure the crotch “tongue” is re-domed over the safety bar.
- 5) Apply the 5-point safety harness, ensuring your toddler is adequately and safely restrained.

**NEVER, UNDER ANY CIRCUMSTANCES LEAVE YOUR CHILDREN UNATTENDED IN THE BUGGY.**

### **SAFETY WARNING:**

The MK3 Toddler seat is to be used with three wheels on **FLAT SURFACES ONLY.** If you are concerned for the stability of the buggy with the (mk3) “top seat” installed, you must purchase the 4-wheel conversion kit to ensure stability and the safety of your children.

**KERB CAUTION:** Extreme care is necessary when moving from the pavement, down a kerb and onto the road. It is advised that for the safest use - Avoid maneuvering the buggy anywhere that you are not able to have all three wheels connecting with the pavement.

**CAUTION:** THE MK3 TODDLER SEAT IS NOT TO BE USED IN ANY CIRCUMSTANCES FOR JOGGING - WALKING PACE ONLY

**EXTREME CAUTION IS ADVISED AT ALL TIMES WHEN USING THIS PRODUCT**



PO Box 30-871  
65 Pharazyn St  
Lower Hutt  
NEW ZEALAND

[www.abcbuggy.co.nz](http://www.abcbuggy.co.nz)  
Email: [abcbuggy@xtra.co.nz](mailto:abcbuggy@xtra.co.nz)